

Datasheet

Spreader LED 6500 Series

Spreader LED for larger yachts.

The powerfull LEDs illuminate with a minimum of power consumption.

The lights are made of turned aluminium.

The surface is anodized or white lacquered. The design fits the curve and angle of modern spreaders.

Light cone 16°= lit-up area diameter 2m.

Port/Starb 16°x43°= lit-up area 2x5m

Power consumption: 3,6W

Colour temperature: 4500k, CRI>80

Lifetime of LED> 40.000h

Internal driver for 12V-24V DC.



Fixing: M5 screws AISI 316 or rivets.
1500mm cable, other length on request.
IP67.

Model	Material	Finish	Bulb	Part. No.
6500	Aluminium	White lacquered	3x1,2W LED	6500-02WH 16
6500	Aluminium	White lacquered	3x1,2W LED	6500-02WH Port
6500	Aluminium	White lacquered	3x1,2W LED	6500-02WH STARB
6508	Aluminium	Black anodized	3x1,2W LED	6508-O2 16
6508	Aluminium	Black anodized	3x1,2W LED	6508-02 PORT
6508	Aluminium	Black anodized	3x1,2W LED	6508-02 STARB
6509	Aluminium	Titan anodized	3x1,2W LED	6509-O2 16
6509	Aluminium	Titan anodized	3x1,2W LED	6509-02 PORT
6509	Aluminium	Titan anodized	3x1,2W LED	6509-02 STARB

Dimensions:

65mm x 44mm x 30mm

2.55in x 1.73in x 1.18in