

## Datasheet

---

### Spreader LED 6600 Series

Spreader LED for larger yachts.

The powerfull LEDs illuminate with a minimum of power consumption.

The lights are made of turned aluminium.

The surface is anodized or white lacquered. Circle housing fits the design of larger spreaders.

Light cone 16°= lit-up area diameter 2m.

Light cone 16° x 43°= lit-up area 2x5m

Power consumption: 3,6W

Colour temperature: 4500k, CRI>80

Lifetime of LED> 40.000h

Internal driver for 12V-24V DC.



Fixing: M5 screws AISI 316 or rivets.  
1500mm cable, other length on request.  
IP67.

Model	Material	Finish	Bulb	Part. No.
6600	Aluminium	White	3x1,2W LED	6600-02WH 16
6600	Aluminium	White lacquered	3x1,2W LED	6600-02WH 16x43
6608	Aluminium	Black anodized	3x1,2W LED	6608-O2 16
6608	Aluminium	Black anodized	3x1,2W LED	6608-0216x43
6609	Aluminium	Titan anodized	3x1,2W LED	6609-O2 16
6609	Aluminium	Titan anodized	3x1,2W LED	6609-02 16x43

Dimensions:  
65mm x 30mm  
2.55in x 1.18in